BARRETT OPTICS

Optical Ranging System (BORS)



Operator's Manual

February 1, 2007

USE OF THIS MANUAL

Before you handle the Barrett Optical Ranging System (BORS), read this manual in its entirety. It is important that you understand the principles of its operation and installation procedures. Important safety topics and equipment care are also addressed. This manual should remain with the BORS and it should be transferred to subsequent owners. Additional manuals can be ordered from Barrett Firearms Manufacturing or can be downloaded from the company web site.

SAFETY GUIDELINES

WARNING
FAILURE TO FOLLOW SAFETY GUIDELINES MAY CAUSE INJURY OR DEATH.

WARRANTY AND SERVICE

Barrett Firearms Manufacturing Inc. (BFMI), warrants that this product was manufactured free of defects in materials and workmanship. For one year from the date of purchase by the original owner, BFMI agrees to correct any defect for the original purchaser by repair or replacement with the same or comparable model.

Technical specifications are subject to change without notice.

If you need factory service, whether made under warranty or not, please contact BFMI for instructions on how to have your BORS repaired.

Barrett Firearms Manufacturing Inc.
P.O. Box 1077
Murfreesboro, TN 37133-1077
615-896-2938

www.barrettrifles.com

TABLE OF CONTENTS

About the Operator's Manual

The BORS manual is organized into 4 main sections:

1. Description of the BORS and battery installation
This section explains the functions of the BORS. Battery installation is also explained. The section outlines operating specifications and storage capacity.

2. Installation and mounting
This section describes how to install the BORS unit on Mil-Std 1913 rail and its host rifle telescope.

3. Keypad usage and screen displays.
This section describes each button on the keypad does and how to use the information on the display screens. This section also explains how to calibrate the unit, "zero" the BORS and scope with live fire, and use the BORS to determine range.

4. Frequently Asked Questions.
This section addresses common issues encountered by first-time users.

Explanation of format and terms used in this manual:

WARNING A WARNING DESCRIBES AN ACTION THAT MAY RESULT IN SERIOUS INJURY OR DEATH.

Caution A caution describes an action that may result in damage to equipment.

Note A note is a recommended operating technique.

Text describing a BORS screen display is "CAPITALIZED AND IN QUOTATIONS".

Barrett Optical Ranging System (BORS) Description

BORS is a ballistic computer that mounts directly to the rifle telescope. The BORS is coupled to the telescope's elevation post. Its body serves as the rear upper scope ring cap.

The BORS continuously measures air temperature, barometric pressure, and bore line angle. Given these inputs, it automatically calculates a ballistic solution for a specific user selected cartridge. The user simply adjusts the BORS elevation knob to match the target's known range with the range displayed on the BORS display. This eliminates the need for "counting clicks" as target ranges change, allowing the shooter to focus on other environmental conditions, and quickly engage multiple targets of varying ranges.

The BORS memory is sufficient to hold 100 cartridge tables. Initialization can be completed in about the same time as it takes to mount a rifle telescope.

Kit Contents

The BORS kit, figure 2-1, includes the following:

- One Barrett Optical Ranging System Computer with factory installed cartridge tables.
- One set of Barrett black anodized aluminum telescope rings
- One lithium ion CR-123 battery
- One BORS operator's manual
- One BORS knob adapter with 3 set screws
- One BORS elevation knob with set screw
- One Tool Kit containing the following:
  - Four 8-32 x 1 1/2" T-25 Torx® socket head cap screws
  - One 10-24 x 1/2" flat head cap screw
  - One 3/32 L-shaped Allen Wrench
  - One T-25 L-shaped Torx® Wrench
  - One tube Loctite® 222 low strength adhesive
  - Four extra 10-24 x ¼" set screws

(Some kits are delivered in a water and air tight case)



Figure 1-1

BORS Technical Specifications

Operating Temperature Range:	-4° F thru 158° F (-20°C thru 70°C)
Weight:	12 oz. (340 grams)
Display:	12 x 2 character liquid crystal
Buttons:	4 Button Keypad
Operating Altitude Range:	-1,000' thru 20,000' (-300 thru 6,100 meters)
Tilt Range:	-90° thru 90° (2° Tilt Resolution)
Battery:	CR-123 Lithium Ion Battery
Battery Life:	30 hours minimum

WARNING
MAKE CERTAIN THE FIREARM IS UNLOADED. REFER TO YOUR FIREARM'S OWNER'S MANUAL TO ENSURE THE FIREARM IS SAFE.

Installing the battery

One CR-123 lithium cell (3.2 Volts) battery is included with the BORS kit. This battery is commonly used for cameras and high-intensity flashlights.



Figure 1-2

Figure 1-3

Note
CR-123 Lithium batteries are recommended for maximum battery life.

Note
Turn the BORS power off before removing the battery. This prevents the loss of previous user selected settings.

1. Rotate the battery cap counter-clockwise to remove the cap from the BORS.
2. Tilt the BORS to the right side to remove any battery in the case.
3. Insert the battery into the case, positive end first.

Caution
Ensure battery cap threads are seated properly to avoid "cross-threading" the aluminum housing.

4. Reattach the battery cap by rotating the cap clockwise into case threads.

Note
The BORS Battery Life Indicator displays a full battery icon when fully charged, a half-full icon when battery life drops below half, and an empty battery icon flashes when it is time to [redacted].

Installing the BOR9 on a typical rifle telescope

WARNING
MAKE CERTAIN THE FIREARM IS UNLOADED. REFER TO YOUR FIREARM'S OWNER'S MANUAL TO ENSURE THE FIREARM IS SAFE.

Note
Ensure that the ring clamp tightening nuts are on the left side. Orient the ring clamp so that the "step cut" side of the clamp bears on the ring and the "angle cut" of the clamp bears on the mounting rail. Do not attempt to remove the nut from the bolt. Figure 2-1.

Figure 2-1

1. Place the rear ring (shipped only as a bottom half) on the M1913 optics mounting rail. Attach this ring on the mounting rail in a slot near the rear of the rail. Figure 2-2. (Proper eye relief may be achieved later by moving the entire assembly.)

Figure 2-2

2. Place the front ring (shipped as an assembled top and bottom) on the M1913 optics mounting rail approximately eight slots forward of the rear ring. From the side view, approximately four complete mounting ridges are visible. Figures 2-2 and 2-3. (Some scope models may require different spacing between rings.)

3. Hand-tighten the cross bolt nuts on both rings to ensure a stable work platform.

4. Using the #25 Torx wrench, remove the top cap on the forward ring.

Figure 2-3

5. Place the scope in the bottom half of the rings. Remove the scope's elevation turret cover if the scope is so equipped. Lightly grasp the scope's elevation knob and rotate it until the knob itself is at the highest point in its adjustment travel. Figure 2-4.



Figure 2-4

Caution

Do not attempt to rotate the rifle scope's elevation knob past its designed mechanical limit.

6. Using the tool provided by the scope manufacturer, remove the screw(s) attaching the scope's elevation knob to its elevation post. Lift and remove the rifle scope's elevation knob to expose the elevation post. Figure 2-5.

Figure 2-5

7. Place the BOFIS knob adapter over the elevation post. Apply a slight downward pressure and tighten the three equally spaced set screws located on the outside of the adapter. Ensure that all set screws are seated below the outside diameter of the knob adapter and are tightened evenly. Use Loctite® if desired. Figure 2-6.



Figure 2-6

8. Place the BORS unit on top of the rear scope ring. Start, but do not tighten, the four socket head cap screws using the T-25 Torx® wrench. Use Loctite® if desired. Figure 2-7

Note
Do not attach the front ring cap until step 13.



Figure 2-7

9. Place the BORS elevation knob over the knob adapter. Push the BORS elevation knob down, seating the knob on the adapter. Ensure the knob rotates without binding. The elevation knob's o-ring serves to align the scope's reticle and align the BORS housing on the scope.

10. Insert one flat head cap screw through the top of the BORS elevation knob engaging the threads in the knob adapter. Excluded: This screw will be removed in all later procedures, only "snug" tighten the flat head cap screw with the T-25 L-shaped Torx® wrench. Figure 2-8. After tightening, rotate the BORS elevation knob to ensure there is no binding during elevation. "Snug" tighten the BORS knob set screw using the .035 L-shaped Allen wrench. Ensure that the flat screw is installed below the outside circumference of the elevation knob.

Figure 2-8

Caution
Do not over-tighten the set screw.

After having ensured that the elevation knob rotates freely, evenly tighten all four Torx® socket head cap screws in the BCR/S unit. [illegible] The goal is to bring the BCR/S housing straight down onto the mounting base so that the BCR/S elevation knob does not bind. Use the tightening sequence as illustrated in Figure 2-9. Tighten to 35 in-lbs or 3.95 Nm.

Tightening Sequence

Figure 2-9

12. Ensure the BCR/S elevation knob rotates freely by turning it until the knob reaches its lowest point. If the elevation knob is binding, loosen the four socket head Torx® screws and repeat step 11.

Caution

Do not attempt to turn the side access's elevation knob past its designed mechanical limit.

13. Fully tighten two socket head cap screws on the mounted side of the front scope ring. Use Loctite® if desired. Tighten to approximately 35 in/lbs. The rings are designed to be fully tightened on the unused side before tightening the opposite side screws. The "Burnell" logo on the top ring can be oriented in either direction. Next, tighten the remaining two socket head Torx® screws on the opposite or "gap" side of the scope ring to 35 in/lbs or 3.95 Nm. Use Loctite® if desired. See figure 2-10.



14. If eye relief needs to be adjusted, loosen the ring clamp nuts to allow the BCH18 and scope to be moved as a unit along the rail to the proper eye relief distance. Retighten the ring clamp nuts to 65 in/lbs or 7.34 Nm. Use Loctite® if desired.

Powering the BORIS on or off

Figure 3-1

Press and hold the ⏻ button as illustrated in Figure 3-1. This will power the BORIS on. Press and hold the button for 5 seconds to power off the BORIS.

When the BORIS powers up, it will display the nine telescope and the version of BORIS computer software. This is the "START-UP SCREEN". It reflects the ballistic tables programmed into the BORIS memory chip and is unique to each rifle system type. This screen is displayed for approximately 3 seconds.

The "START UP SCREEN" Figure 3-2 shows a BORIS configured for a BARRETT M107 in .50 Caliber.



Figure 3-2

Operator's Screen

The screen displayed immediately following the start-up screen is the "OPERATOR'S SCREEN". This screen displays the cartridge type that the BORS computer is using to calculate the bullet drop solution. The "OPERATOR'S SCREEN" is the BORS default screen.

Displayed in the upper left corner of the display is the selected cartridge type.

Displayed in the upper right corner of the display is the numerical range at which the cartridge's bullet drop and the scope's horizontal reticle coincide. This range can be displayed in either yards, expressed as "y" or in meters expressed as "m". The procedure used to change the measurement basis is described on page 21.

In the lower portion of the "OPERATOR'S SCREEN" is displayed either an "I" if the rifle is level or a "T" if the shooter needs to cant the rifle to achieve level. The roll sensor is calibrated at the factory.



Figure 3-4 illustrates the BORS when the firearm is tilted to the left.

Figure 3-5 illustrates the BORS when the firearm is level.

Figure 3-6 illustrates the BORS when the firearm is tilted to the right.

The BORIS pitch sensor, which has no user display, senses the angle of inclination or declination of the rifle's bore line. The BORIS automatically adjusts the ballistic solution to compensate for changes in this angle. The pitch sensor is calibrated at the factory.

Note
If the digital level is not working properly, contact Barrett for assistance.

NOTE
The displayed range on the operations screen is only valid if the carriage tilt at level is the same as is selected in the BORIS



Figure 3-7

Figure 3-7 shows a BORIS using a M82A1 carriage balanced ballistic solution that has calculated a bullet drop solution that provides bullet impact at 100 meters consistent with the horizontal reticle. The rifle is level.



Figure 3-8

From the "OPERATOR'S SCREEN" press the button illustrated in Figure 3-8. This will display the current temperature and barometric pressure.

BOP5 Button Functions

The four button keypad is used to access BOP5 information and displays. Their function depends on whether the cartridge identification screen is displayed when the button is depressed or another screen is displayed when the button is depressed.

The following commands are active if the "OPERATOR'S SCREEN" is displayed when a keypad button is depressed:

1. ⏻ Power On/Off
2. Display temperature and barometric pressure.
3. Power on the LCD back light.
4. Select display screen menus.

The following commands are active if any screen other than the "OPERATOR'S SCREEN" is displayed when the keypad button is depressed:

1. ⏻ Scroll menu down
2. Select menu item.
3. Scroll menu UP
4. Select display screen menus.

Title	Icon	Function
Menu		Used to access BOP5 display menus
Temperature/Select		Displays temperature, barometric pressure, and select menu item.
Light/Scroll Up		Illuminates the display and scrolls the menu up
Power/Scroll Down	⏻	Powers the BOP5 on, off, and scrolls the menu down

Press the [F] button as illustrated in Figure 3-9. This will allow access to one of six display screens. The screens are accessed by either scrolling up [↑] or scrolling down [↓]. The screens are arranged in the following order: "ZERO CARTRIDGE" "DETERMINE RANGE" "SELECT CARTRIDGE" "CARTRIDGE INFORMATION" "CHANGE UNITS" and "CHANGE SETTINGS". If [F] is pressed again the EORS computer will exit the current selection and return to the previous display.



Figure 4-7

SELECT CARTRIDGE

Press and release the ⏻ button.

2 Press and release the ˙ button until the display reads: SELECT CARTRIDGE

3 Press and release the button to select the menu item. The currently selected cartridge will be displayed as illustrated in Figure 3- 6. The cartridge description is displayed under the cartridge name. Depending on the length of the description, the words may scroll across the screen.

4 Using the arrow buttons, ˆ or ˇ, scroll to the desired cartridge. Press and release the button when the desired cartridge is displayed.

The screen will display "<CONFIRM CARTRIDGE>" as previously illustrated.

Press and release the button to confirm or the ⏻ button to cancel. The selected cartridge will be displayed on the "OPERATOR'S SCREEN" after confirmation.

Figure 3-6

CHANGE UNITS

Changing Units of Measurement Basis

BDRS displays units of measurement on all screens based on either Metric or U.S equivalents. To change from the currently displayed basis to the other basis:

1. Press the button
2. Press the or button until the display reads "CHANGE UNITS.
3. Press the button to change the basis from the current to the other basis

> **Note**
> The user can confirm changing measurement basis by viewing the range units displayed on the OPERATOR'S SCREEN as either "m" or "Y".

Displayed Metric and U.S. Equivalents

Units	Range	Temperature	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
US	Yards	Fahrenheit	Inches of Mercury	Feet per second	Inches	Grains	Feet
Metric	Meters	Celsius	Millibars	Meters per second	Millimeters	Grams	Meters

Figure 3-

CHANGE SETTINGS

Note

Calibrating the BORS to your rifle telescope is necessary any time power is lost to the BORS unit.

Caution

Do not attempt to turn the elevation knob past its designed mechanical limit.

Calibrating the BORS to your rifle telescope

1. Rotate the BORS elevation knob clockwise until it reaches its lowest point.
2. Press the button to enter the menu screen.
3. Press the button until the screen displays "CHANGE SETTINGS".
4. Press the button. The screen will display "ADJUST BACKLIGHT".
5. Press the button once. The screen will display "DEVICE SETUP". Press the button to select this screen.
6. Press the button to display "ZERO ELEVATION".
7. Press the button to confirm the selection. The BORS is now calibrated to your rifle telescope.

Adjusting the backlight

1. Press the button to enter the menu screen.
2. Press the button until the screen displays "CHANGE SETTINGS". Press the button to select this screen.
3. The screen displays "ADJUST BACKLIGHT". Press the button to select this screen.
4. The screen displays "BACKLIGHT SCROLL UP/DN". See Figure 3-12.
5. Press the or the button to adjust the display brightness.

Checking the version of BORS

1. Press the button to enter the menu screen.
2. Press the button until the screen displays "CHANGE SETTINGS".
3. Press the button. The screen will display "ADJUST BACKLIGHT".
4. Press the button twice to display "VERSION INFORMATION".
5. Press the button to display currently installed hardware and firmware versions.

Adjusting the Contrast

Press the button to enter the menu screen

2. Press the button until the screen displays "CHANGE SETTINGS" Press the button.
3. The screen will display "ADJUST BACKLIGHT"
4. Press the button. The screen will display "ADJUST CONTRAST" Press the button to select this screen
5. The screen displays "CONTRAST SCROLL UP/DN" See Figure 3-19
6. Press the or the button to adjust the display contrast.

Figure 3-19



Figure 3-20

Adjusting the backlight timer (The length of time the backlight will illuminate)

Press the button to enter the menu screen

2. Press the button until the screen displays "CHANGE SETTINGS
3. Press the button. The screen will display "ADJUST BACKLIGHT"
4. Press the button. This will display "DEVICE SETUP"
5. Select this display by pressing the button. "ZERO ELEVATION" will be displayed
6. Now press the button to display "BACKLIGHT TIMER"
7. Press the button to select this screen.
8. Use the or the button to adjust the time the backlight remains illuminated

CARTRIDGE INFORMATION

1. Press and release the "9" button to enter the menu screen.
2. Press the $\bar{}$ or the button until the screen displays "CARTRIDGE INFORMATION"
3. Press and release the button. "DESCRIPTION" is shown on the top line of the display. Below "DESCRIPTION:" will be displayed a user-defined summary of the cartridge. Depending on the length of the description, the words may scroll across the screen.
4. Pressing the or the $\pm$ button will display the "CALIBER" "BULLET WT." "BULLET B.C." or "MUZZLE VELOCITY" of the cartridge selected.

ZERO CARTRIDGE

Point of impact zeroing procedure for the BORS on the fire fire range

The zeroing procedure for the BORS is similar to zeroing any common rifle telescope. The optimal distance for zeroing the cartridge point of impact is 100 meters or 110 yards. The following steps zero the BORS with a specific cartridge, rifle and rifle telescope.

Step 1

Select the desired cartridge on the BORS "SELECT CARTRIDGE" screen. Fire a series of shots to obtain a representative group of point of impact with true cartridge type.

Step 2

Adjust the BORS elevation knob until the projectile's point of impact coincides with the rifle telescope's horizontal reticle. If desired, adjust the rifle scope's left/right knob until the projectile's point of impact coincides with the rifle telescope's vertical reticle. The BORS has no influence on windage adjustments.



Figure 1-14

Step 3

Loosen the set screw and the nut located below on the BORS elevation knob. Figure 3- 5. The elevation knob and index spindle freely on the BORS knob adapter but will not index the reticle. Rotate the BORS elevation knob until its "0" mark index line is coincident with either index line located on the outside of the BORS housing. It is user preference whether the left or right side housing index line is used. Hold the BORS elevation knob in position and tighten the set screw first and then tighten the nut. Hold screw second. You may now set the cartridge and the riflescope's [illegible] knob.

Figure 3-5

Note

Do not move the BORS knob when the BORS is powered off. If the BORS knob is moved while the unit is powered off, you must return the BORS elevation knob to its reference zero position, then restore power to the BORS to accomplish "Calibrating the BORS to your rifle/riflescope" on page 21.

Step 4

To initialize the BORS to a selected cartridge, press the Φ button. Press the button until the screen displays "ZERO CARTRIDGE". Press the button to select this screen.

Figure 3-6

The screen will now display "<-CONFIRM CANCEL->". Press the button to confirm. Press the Φ button to return to the "OPERATOR'S SCREEN". After confirming, the display will indicate "100 m" or "10 y" depending on the measurement basis.

DETERMINE RANGE

Determining the Range to the Target with the BCATS

BCATS provides the operator the ability to measure and then display the range to a reference object or target. This distance can be displayed in either yards or meters. The known vertical dimension of the reference object is used to calculate the distance to that object.

Note
Range measurements will be most accurate when the ship is held steady and a large reference object is selected.

Figure 1-17 shows the reference object as a vehicle known to be approximately 6 feet tall. The user selects "6 FEET" as the height of the reference object. Using the BCATS elevation knob to adjust the elevation cursor, bring the height of the vehicle. The BCATS is able to calculate the distance to the vehicle.

Range Finding Procedure:

1. Press the [illegible] button to enter the menu screen.
2. Press the [illegible] button until the screen displays "DETERMINE RANGE".
3. Press the [illegible] button to select this function.

4. The screen will display "TARGET SIZE?" on the top line. The bottom line will display either "1 FOOT" or "1 METER" depending on selected measurement units.

5. By pressing the [illegible] or the [illegible] button the user can adjust to display the approximate vertical size of a reference object. If [illegible] measurements have been selected, "1 FOOT", "2 FEET", "3 FEET", "4 FEET", "5 FEET", and "6 FEET" will be displayed. If metric units have been selected, "1 meter", "1 METER", "2 METERS", "3 METERS", "4 METERS", "5 METERS", and "6 METERS" will be displayed.

1. From a steady rest, position the horizontal crosshairs at the top or bottom of the reference object. Press the $\frac{L}{\pm}$ button to select the height of the reference object. "MEASURE TRGT USING ELEV" will be displayed.



Figure 3-17



Figure 3-18

2. Using the BDRS elevation knob, move the horizontal crosshair either from the top of the reference object to its bottom, or from the bottom of the object to its top as illustrated in Figure 3-18.

NOTE

The measurement will be most accurate when the rifle is kept steady throughout the procedure.

3. Press the $\frac{L}{\pm}$ button to display the range to the reference object. The distance to the reference object will be displayed as "TARGET RANGE 1012 YARDS" as illustrated in Figure 3-19.



Figure 3-19

4. Press the $\square$ button to return to the "OPERATOR'S SCREEN". Use the BDRS elevation knob to dial the reference object's range. Your riflescope elevation crosshairs are now adjusted so that your point of aim is the point of impact at the reference object's calculated range.

Frequently Asked Questions

Why are my bullets striking consistently higher or lower than my point of aim?
Make sure the cartridge being used is the same one as displayed on the "OPERATOR'S SCREEN". If correct, reaccomplish the procedures on page 22, "calibrating the BORS". If the problem persists, reaccomplish the procedures on page 28, point of impact zeroing procedure for the BORS.

The BORS loses power, the battery fails, the display screen is unreadable or the BORS unit fails. What should I do?
The BORS is designed so that your rifle telescope is fully functional even in the event of battery or BORS unit failure. If time permits, remove and replace the battery, then follow the instructions on page 22, "calibrating the BORS". This will restore previous settings. If time does not permit, the user may visually reference an index mark and elevation graduations on the BORS knob to obtain the rifle telescope's internal elevation setting.

Why does the display range fluctuate?
The BORS sensors are reacting to constantly changing environmental conditions. These changes are continuously updated and displayed as small changes in range.

Why does the display not change after an audible scope click?
It is possible for the display to not change after a click. The BORS reacts for BORS elevation knob graduations, not internal scope clicks. The user can synchronize the clicks with the graduations by adjusting the index marks as illustrated Figure 3-15 on page 27.

When if the BORS knob is moved when the BORS is not powered?
Moving the BORS elevation knob while the BORS is not powered requires the user to recalibrate the BORS. To recalibrate the BORS, first return the BORS elevation knob to reference zero, then restore power to the BORS. Now accomplish "calibrating the BORS" on page 22.

Can I set the BORS for multiple cartridges?
Yes, the BORS can hold as many as 100 individual ballistic tables.